



STATE OF IDAHO  
DEPARTMENT OF  
ENVIRONMENTAL QUALITY

1410 North Hilton • Boise, Idaho 83706-1255 • (208) 373-0502

Dirk Kempthorne, Governor  
Toni Hardesty, Director

June 27, 2005

**Certified Mail No. 7000 1670 0013 8128 2794**

Patrick Clark  
Environmental Advisor  
Staker & Parsons Companies  
P.O. Box 3429  
Ogden, UT 84409

RE: Facility ID No. 777-00140, Jack B. Parson Companies, Pocatello  
Final Permit Letter

Dear Mr. Clark:

The Idaho Department of Environmental Quality (DEQ) is issuing Permit to Construct (PTC)/Tier II Permit Number P-040319 for Jack B. Parson Companies, in accordance with IDAPA 58.01.01.200 through 228 (Rules for the Control of Air Pollution in Idaho).

This permit is based on your permit application received on December 30, 2004. This permit is effective immediately and replaces your previous permit number T2-030306, issued on July 11, 2003. This permit does not release Jack B. Parsons Companies from compliance with all other applicable federal, state, or local laws, regulations, permits, or ordinances.

Since this project does not significantly change the terms of your permit, DEQ will not contact you regarding a meeting to discuss the terms of the permit. However, if you wish to meet to discuss the permit terms and requirements, you may contact Pete Wagner, Regional Air Quality Manager, of the Pocatello Regional Office to schedule a meeting. If a meeting is scheduled, DEQ recommends the following representatives attend the meeting: your facility's plant manager, responsible official, environmental contact, and any operations staff responsible for day-to-day compliance with permit conditions.

Pursuant to IDAPA 58.01.23, you, as well as any other entity, may have the right to appeal this final agency action within 35 days of the date of this decision. However, prior to filing a petition for a contested case, I encourage you to call Dan Pitman, Regional Permit Coordinator, at (208) 373-0502 to address any questions or concerns you may have with the enclosed permit.

Sincerely,

Martin Bauer, Administrator  
Air Quality Division

MB/DM/sd  
Enclosures

Permit No. P-040319



**Air Quality  
Tier II Operating Permit  
and  
Permit To Construct**

**State of Idaho  
Department of Environmental Quality**

**Permit No. P-040319**

**AIRS Facility No.: 777-00140**

**AQCR: Portable CLASS: SM**

**SIC: 2951 ZONE: Portable**

**UTM COORDINATE (km): Portable**

**1. PERMITTEE**

Jack B. Parson Companies.

**2. PROJECT**

Tier II Permit and Permit to Construct

**3. MAILING ADDRESS**

P. O. Box 4002

**CITY**

Pocatello

**STATE**

ID

**ZIP**

83205

**4. FACILITY CONTACT**

Patrick Clark

**TITLE**

Environmental Advisor

**TELEPHONE**

(801) 409-2415

**5. RESPONSIBLE OFFICIAL**

Chuck Lindsay

**TITLE**

Operations Manager

**TELEPHONE**

(801) 232-5796

**6. EXACT PLANT LOCATION**

Portable

**COUNTY**

Portable

**7. GENERAL NATURE OF BUSINESS & KINDS OF PRODUCTS**

Hot-Mix Asphalt Plant

**8. PERMIT AUTHORITY**

This permit is issued according to the *Rules for the Control of Air Pollution in Idaho*, IDAPA 58.01.01.200 et seq. and IDAPA 58.01.01.400 et seq. This permit pertains only to emissions of air contaminants regulated by the state of Idaho and to the sources specifically allowed to be operated by this permit.

This permit is not transferable to another person, place, or piece or set of equipment. This permit will expire if construction has not yet begun within two years of its issue date or if construction is suspended for one year.

This permit has been granted on the basis of design information presented in the application and the Idaho Department of Environmental Quality's (DEQ) technical analysis of the supplied information. Changes in design or equipment that result in any change in the nature or amount of emissions may be considered a modification. Modifications are subject to DEQ review in accordance with IDAPA 58.01.01.200.

  
TONI HARDESTY, DIRECTOR  
DEPARTMENT OF ENVIRONMENTAL QUALITY

**DATE ISSUED: June 27, 2005**

**DATE EXPIRES September 18, 2007**

## Table of Contents

ACRONYMS, UNITS, AND CHEMICAL NOMENCLATURE .....	3
1. PERMIT SCOPE .....	4
2. FACILITY-WIDE CONDITIONS .....	5
3. HOT- MIX ASPHALT DRYER .....	8
5. FACILITY EMISSION RATE LIMITS SUMMARY .....	13
6. FACILITY EMISSION INVENTORY .....	14
7. GENERAL PROVISIONS .....	15

## **Acronyms, Units, and Chemical Nomenclature**

AQCR	Air Quality Control Region
ASTM	American Society of Testing and Materials
CO	carbon monoxide
DEQ	Department of Environmental Quality
CFR	Code of Federal Regulations
gr/dscf	grains per dry standard cubic feet
EPA	Environmental Protection Agency
IDAPA	A numbering designation for all administrative rules in Idaho promulgated in accordance with the Idaho Administrative Procedures Act
km	kilometer
lb/hr	pounds per hour
mg/kg	milligrams per kilogram
NO <sub>x</sub>	nitrogen oxides
NSPS	New Source Performance Standards
O&M	Operation and Maintenance
PM	particulate matter
PM <sub>10</sub>	particulate matter with an aerodynamic diameter less than or equal to a nominal 10
ppm	parts per million
RCRA	Resource Conservation and Recovery Act
SIC	Standard Industrial Classification
SO <sub>2</sub>	sulfur dioxide
SO <sub>x</sub>	sulfur oxides
T/day	tons per day
T/hr	tons per hour
T/yr	tons per year
UTM	Universal Transverse Mercator
VOC	volatile organic compound

**AIR QUALITY TIER II OPERATING PERMIT AND PERMIT TO CONSTRUCT NUMBER: P-040319**

<b>Permittee:</b>	Jack B. Parson Companies	<b>Facility ID No:</b>	<b>Date Issued:</b>	<b>June 27, 2005</b>
<b>Location:</b>	Portable	777-00140	<b>Date Expires:</b>	<b>September 18, 2007</b>

**1. PERMIT SCOPE*****Purpose***

- 1.1 The purpose of this Tier II Operating Permit and Permit to Construct is to modify the facility's existing Tier II/PTC permit, limit facility emissions to below major facility classification, protect ambient air quality standards, and allow the facility to remediate soil and aggregate materials that have been contaminated by on-specification used oil. The facility is already permitted to remediate aggregate and soil contaminated by gasoline, diesel fuel oil, and residual fuel oil while producing hot-mix asphalt.
- 1.2 This permit incorporates and replaces the following permit, the terms and conditions of which are no longer in effect:
- Tier II Operating Permit/Permit to Construct No. T2-030306, issued July 18, 2003.

***Regulated Sources***

- 1.3 Table 1.1 below lists all sources of emissions that are regulated in this permit:

**Table 1.1 REGULATED EMISSIONS SOURCES**

<b>Permit Section</b>	<b>Source Description</b>	<b>Emissions Controls</b>
3	Hot-Mix asphalt plant dryer, Cedarapids drum mix, 450-T/hr capacity	Standard Havens baghouse, Model: Alpha Mark III

***Unregulated Sources***

- 1.4 Table 1.2 below lists sources of emissions that do not require specific permit limits.

**Table 1.2 UNREGULATED EMISSIONS SOURCES**

<b>Source Description</b>
Fuel oil tanks
Fugitive emission sources (e.g., roads, piles, material transfers)

AIR QUALITY TIER II OPERATING PERMIT AND PERMIT TO CONSTRUCT NUMBER: P-040319				
Permittee:	Jack B. Parson Companies	Facility ID No:	Date Issued:	June 27, 2005
Location:	Portable	777-00140	Date Expires:	September 18, 2007

## 2. FACILITY-WIDE CONDITIONS

### *Fugitive Emissions*

#### 2.1 Reasonable Control of Fugitive Emissions

All reasonable precautions shall be taken to prevent PM from becoming airborne as required in IDAPA 58.01.01.651. In determining what is reasonable, considerations will be given to factors such as the proximity of dust-emitting operations to human habitations and/or activities and atmospheric conditions that might affect the movement of PM. Some of the reasonable precautions include, but are not limited to, the following:

- Use, where practical, of water or chemicals for control of dust in the demolition of existing buildings or structures, construction operations, the grading of roads, or the clearing of lands.
- Application, where practical, of asphalt, oil, water or suitable chemicals to, or covering of, dirt roads, material stockpiles, and other surfaces which can create dust.
- Installation and use, where practical, of hoods, fans, and fabric filters or equivalent systems to enclose and vent the handling of dusty materials. Adequate containment methods should be employed during sandblasting or other operations.
- Covering, where practical, of open-bodied trucks transporting materials likely to give rise to airborne dusts.
- Paving or roadways and their maintenance in a clean condition, where practical.
- Prompt removal of earth or other stored material from streets, where practical.

### *Visible Emissions*

#### 2.2 Reasonable Control Measures

The permittee shall monitor and record the periodic method(s) used to reasonably control emissions from this facility during operation. The record shall include the type of control used (e.g., water, environmentally safe chemical dust suppressants, etc.), as well as the circumstances under which no controls are used.

- 2.3 No person shall discharge any air pollutant to the atmosphere from any point of emission for a period or periods aggregating more than three minutes in any 60-minute period which is greater than 20% opacity as determined by procedures contained in IDAPA 58.01.01.625. These provisions shall not apply when the presence of uncombined water, NO<sub>x</sub>, and/or chlorine gas is the only reason(s) for the failure of the emissions to comply with the requirements of this section.

**AIR QUALITY TIER II OPERATING PERMIT AND PERMIT TO CONSTRUCT NUMBER: P-040319**

<b>Permittee:</b>	Jack B. Parson Companies	<b>Facility ID No:</b>	<b>Date Issued:</b>	<b>June 27, 2005</b>
<b>Location:</b>	Portable	777-00140	<b>Date Expires:</b>	<b>September 18, 2007</b>

- 2.4 Unless specified elsewhere in this permit, the permittee shall conduct a quarterly facility-wide inspection of potential sources of visible emissions during daylight hours and under normal operating conditions. The inspection shall consist of a see/no see evaluation for each potential source. If any visible emissions are present from a point of emission, the permittee shall either take appropriate corrective action as expeditiously as practicable or perform a Method 9 opacity test in accordance with the procedures outlined in IDAPA 58.01.01.625. A minimum of 30 observations shall be recorded when conducting the opacity test. If opacity is greater than 20% for a period or periods aggregating more than three minutes in any 60-minute period, the permittee shall take all necessary corrective actions and report the exceedance in accordance with IDAPA 58.01.01.130-136. The permittee shall maintain records of the results of each quarterly visible emission inspection and each opacity test when conducted. The records shall include, at a minimum, the date and results of each inspection and test, and a description of the following: The permittee's assessment of the conditions existing at the time visible emissions are present (if observed), any corrective action taken in response to the visible emissions, and the date corrective action was taken.

***Excess Emissions***

- 2.5 The permittee shall comply with the procedures and requirements of IDAPA 58.01.01.130-136 for excess emissions due to startup, shutdown, scheduled maintenance, safety measures, upsets, and breakdowns.

***Monitoring and Recordkeeping***

- 2.6 The permittee shall maintain sufficient recordkeeping to assure compliance with all of the terms and conditions of this operating permit. Records of monitoring information shall include, but not be limited to the following: (a) the date, place, and times of sampling or measurements; (b) the date analyses were performed; (c) the company or entity that performed the analyses; (d) the analytical techniques or methods used; (e) the results of such analyses; and (f) the operating conditions existing at the time of sampling or measurement. All monitoring records and support information shall be retained for a period of at least five years from the date of the monitoring sample, measurement, report, or application. Supporting information includes, but is not limited to, all calibration and maintenance records, all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. All records required to be maintained by this permit shall be made available in either hard copy or electronic format to DEQ representatives upon request.

***Reports and Certifications*****2.7 Relocation**

All existing portable equipment shall be registered. At least 10 days prior to relocation of any equipment covered by this permit, the permittee shall submit a scaled plot plan and, in accordance with IDAPA 58.01.01.500, a complete Portable Equipment Registration and Relocation Form (available from DEQ website at <http://www2.state.id.us/deq/air/>) to the following:

PERF Processing Unit  
Idaho Department of Environmental Quality  
1410 N. Hilton  
Boise, ID 83706-1255

<b>AIR QUALITY TIER II OPERATING PERMIT AND PERMIT TO CONSTRUCT NUMBER: P-040319</b>				
<b>Permittee:</b>	Jack B. Parson Companies	<b>Facility ID No:</b>	<b>Date Issued:</b>	<b>June 27, 2005</b>
<b>Location:</b>	Portable	777-00140	<b>Date Expires:</b>	<b>September 18, 2007</b>

### ***Sulfur Content***

- 2.8 No person shall sell, distribute, use, or make available for use any fuel oil containing more than the following percentages of sulfur:
- ASTM Grade 1 fuel oil - 0.3% by weight.
  - ASTM Grade 2 fuel oil - 0.5% by weight.
  - Residual fuel oil (ASTM Grade 4, 5, and 6) – 1.75% by weight.
- 2.9 The permittee shall maintain documentation of supplier verification of fuel oil sulfur content on an as-received basis.

### ***Air Stagnation Advisory Days***

- 2.10 The permittee shall comply with the Air Pollution Emergency Rules in IDAPA 58.01.01.550 through 562.



**AIR QUALITY TIER II OPERATING PERMIT AND PERMIT TO CONSTRUCT NUMBER: P-040319**

<b>Permittee:</b>	Jack B. Parson Companies	<b>Facility ID No:</b>	<b>Date Issued:</b>	<b>June 27, 2005</b>
<b>Location:</b>	Portable	777-00140	<b>Date Expires:</b>	<b>September 18, 2007</b>

**3. HOT-MIX ASPHALT DRYER**

The permittee shall comply with the following sourcewide conditions when the hot-mix asphalt facility is operated anywhere (nonattainment, attainment, or unclassifiable areas) within the state of Idaho.

**3.1 Process Description**

This is a hot-mix asphalt plant for asphalt production and soil remediation.

**3.2 Control Description**

The dryer is controlled by a baghouse. Fugitive emissions are controlled by best management practices.

***Emissions Limits*****3.3 Asphalt Dryer Emission Limits**

The PM emissions from the hot-mix asphalt dryer stack shall not exceed 0.04 gr/dscf, nor shall PM<sub>10</sub>, CO, NO<sub>x</sub>, and SO<sub>2</sub> emissions from the hot-mix asphalt dryer stack exceed any corresponding emission rate limit listed in Permit Condition 5.

**3.4 Other Particulate Matter Emission Limits**

Gases from systems for screening, handling, storing, and weighing hot aggregate that emanate from a stack, vent, or other functionally equivalent opening shall not contain PM emissions in excess of 0.04 gr/dscf.

***Operating Requirements*****3.5 Facility Production Limits**

The production rate of the hot-mix asphalt plant shall not exceed a maximum of 936,000 tons per consecutive 12-month period, whether located alone or in combination with the rock crushing plant.

**3.6 Non-Attainment Area Production Limits**

- The production rate of the hot-mix asphalt plant shall not exceed a maximum of 3,195 tons per consecutive 24-hour period (T/day) when co-located with the rock crushing plant in any PM<sub>10</sub> non-attainment area, or proposed PM<sub>10</sub> non-attainment area.
- The production rate of the hot-mix asphalt plant shall not exceed a maximum of 6,194 tons per consecutive 24-hour period (T/day), when located alone, in any PM<sub>10</sub> non-attainment area, or proposed PM<sub>10</sub> non-attainment area.

**3.7 Dryer Burner Fuel Limits**

The burner fuel shall be either residual fuel (ASTM Grade 4, 5, or 6), distillate fuel (ASTM Grade 1 or 2), or used oil only.

**AIR QUALITY TIER II OPERATING PERMIT AND PERMIT TO CONSTRUCT NUMBER: P-040319**

<b>Permittee:</b>	Jack B. Parson Companies	<b>Facility ID No:</b>	<b>Date Issued:</b>	<b>June 27, 2005</b>
<b>Location:</b>	Portable	777-00140	<b>Date Expires:</b>	<b>September 18, 2007</b>

**3.8 Monitoring Equipment**

The permittee shall install, calibrate, maintain, and operate, in accordance with manufacturer specifications, equipment to continuously measure the pressure differential across the baghouse.

**3.9 Operations and Maintenance Manual Requirements**

Within 60 days of the issuance of this permit, the permittee shall have developed an O&M manual for the air pollution control device which describes the procedures that will be followed to comply with General Provision 2 and the baghouse requirements contained in this permit. The manual shall remain onsite at all times and shall be made available to DEQ representatives upon request.

**3.10 Pressure Drop Across Air Pollution Control Device**

The pressure drop across the baghouse shall be maintained within manufacturer and O&M manual specifications. Documentation of both the manufacturer and O&M manual operating pressure drop specifications shall remain onsite at all times and shall be made available to DEQ representatives upon request.

**3.11 Used Oil Specifications**

The concentrations/parameters of contaminants in any used-oil fuel or used oil-contaminated soil or aggregate shall not exceed the following levels, as defined in 40 CFR 279.11:

Arsenic	5 ppm by weight
Cadmium	2 ppm by weight
Chromium	10 ppm by weight
Lead	100 ppm by weight
Total halogens	1,000 ppm by weight

**3.12 Used Oil Sulfur Content**

The sulfur content of the used oil shall not exceed 0.66% by weight.

**3.13 Sandpoint PM<sub>10</sub> Nonattainment Area**

The permittee shall not locate the portable hot mix asphalt plant in the Sandpoint PM<sub>10</sub> nonattainment area. The permittee may submit an air quality permit to construct application which requests the ability to locate this facility within the Sandpoint PM<sub>10</sub> nonattainment area.

***Monitoring and Recordkeeping Requirements*****3.14 Operating Parameters**

The following parameters shall be monitored and recorded:

AIR QUALITY TIER II OPERATING PERMITAND PERMIT TO CONSTRUCT NUMBER: P-040319				
<b>Permittee:</b>	Jack B. Parson Companies	<b>Facility ID No:</b>	<b>Date Issued:</b>	June 27, 2005
<b>Location:</b>	Portable	777-00140	<b>Date Expires:</b>	September 18, 2007

- Pressure drop across the baghouse on a daily basis.
- Hot-mix asphalt production in tons per day and tons per month.

### **3.15 Analysis of Used Oil Fuel**

The permittee shall demonstrate compliance with Permit Conditions 3.11 and 3.12 by performing analyses or obtaining copies of analyses or other information for each used oil delivery documenting that the used oil fuel meets the specifications.

AIR QUALITY TIER II OPERATING PERMIT AND PERMIT TO CONSTRUCT NUMBER: P-040319				
Permittee:	Jack B. Parson Companies	Facility ID No:	Date Issued:	June 27, 2005
Location:	Portable	777-00140	Date Expires:	September 18, 2007

#### 4. PERMIT REQUIREMENTS FOR REMEDIATING PETROLEUM-CONTAMINATED SOILS AND AGGREGATES

The permittee shall comply with Permit Conditions 3.1 through 3.15 and the following permit requirements whenever the hot-mix asphalt facility remediates used oil and petroleum-contaminated soils and aggregates for subsequent hot-mix asphalt production.

##### ***Operating Requirements***

##### 4.1 Petroleum-Contaminated Soil and Aggregate Throughput Limit

The maximum amount of petroleum-contaminated soil and aggregate to be remediated by the hot-mix asphalt facility shall not exceed 87,000 tons per any consecutive 12-month period.

The maximum amount of used oil-contaminated soil and aggregate to be remediated shall not exceed 4,800 tons per any consecutive 24-hour period. The permittee shall comply with the hot mix asphalt production limitations specified in Permit Condition 3.6 while operating in a PM<sub>10</sub> non-attainment area.

All remediated materials shall be used in conjunction with the production of asphalt.

##### 4.2 Gasoline Concentration

The gasoline concentration in any petroleum-contaminated soil and aggregate to be remediated shall not exceed 5,000 mg/kg.

##### 4.3 Used Oil-Contaminated Soil and Aggregate

The permittee shall not remediate used oil-contaminated soil or aggregate material that is a RCRA hazardous waste.

##### ***Monitoring and Recordkeeping Requirements***

##### 4.4 Petroleum Contaminated Soil and Aggregate

The permittee shall monitor and record the amount of petroleum-contaminated soil and aggregate remediated by this hot-mix asphalt facility on a monthly and annual basis to demonstrate compliance with Permit Condition 4.1. The throughput shall be recorded as tons per month, and tons per any consecutive 12-month period (T/yr).

##### Used Oil Contaminated Soil and Aggregate

The permittee shall monitor and record the amount of used oil-contaminated soil and aggregate remediated by this hot-mix asphalt facility on daily, monthly, and annual bases in units of tons per day, tons per month, and tons per any consecutive 12-month period (T/yr).

AIR QUALITY TIER II OPERATING PERMITAND PERMIT TO CONSTRUCT NUMBER: P-040319				
Permittee:	Jack B. Parson Companies	Facility ID No:	Date Issued:	June 27, 2005
Location:	Portable	777-00140	Date Expires:	September 18, 2007

**4.5 Gasoline Concentration and Used Oil Contaminant Monitoring**

All petroleum product and used oil-contaminated soil and aggregate to be remediated by this hot-mix asphalt facility shall be analyzed by an independent laboratory to demonstrate compliance with Permit Conditions 3.11 and 4.2.

**AIR QUALITY TIER II OPERATING PERMIT AND PERMIT TO CONSTRUCT NUMBER: P-040319**

<b>Permittee:</b>	Jack B. Parson Companies	<b>Facility ID No:</b>	<b>Date Issued:</b>	<b>June 27, 2005</b>
<b>Location:</b>	Portable	777-00140	<b>Date Expires:</b>	<b>September 18, 2007</b>

**5. FACILITY EMISSION RATE LIMITS SUMMARY**

Table 5.1 provides the emission rate limits for the sources in this permit.

**Table 5.1 EMISSION RATE LIMITS**

Source Description	Emissions Limits <sup>a</sup> – Hourly (lb/hr) and Annual (T/yr) <sup>b</sup>							
	PM <sub>10</sub> <sup>c</sup>		CO		NO <sub>x</sub>		SO <sub>2</sub>	
	lb/hr	T/yr	lb/hr	T/yr	lb/hr	T/yr	lb/hr	T/yr
Asphalt Dryer	6.7	6.9	16.2	16.9	33.7	35.1	88.2	91.8

<sup>a</sup> Compliance determined by a pollutant-specific U.S. EPA reference method, DEQ-approved alternative, or as determined by DEQ's emissions estimation methods used in this permit analysis.

<sup>b</sup> Compliance with annual limits determined by multiplying the actual or allowable (if actual is not available) pound-per-hour emission rate by the allowable hours per year that the process(es) may operate(s), or by actual annual production rates.

<sup>c</sup> PM<sub>10</sub> limits include condensables.

**AIR QUALITY TIER II OPERATING PERMIT AND PERMIT TO CONSTRUCT NUMBER: P-040319**

<b>Permittee:</b>	Jack B. Parson Companies	<b>Facility ID No:</b>	<b>Date Issued:</b>	<b>June 27, 2005</b>
<b>Location:</b>	Portable	777-00140	<b>Date Expires:</b>	<b>September 18, 2007</b>

**6. FACILITY EMISSION INVENTORY**

Table 6.1 provides a summary of the emission inventory for criteria air pollutants based on the potential to emit when collocated with the portable rock crushing plant, Operating Permit No. 777-00141. Any limitations imposed by this permit are included in calculating potential to emit. This table is for informational purposes only.

**Table 6.1 FACILITY EMISSIONS INVENTORY**

Source	PM <sub>10</sub> <sup>c</sup>	SO <sub>2</sub>	CO	NO <sub>x</sub>	VOC
	T/yr	T/yr	T/yr	T/yr	T/yr
Asphalt dryer	6.9	91.8	16.9	35.1	NA
Rock crushers	46.0				
Generator	0.8	7.2	11.6	44.4	NA
<b>Total</b>	<b>53.7</b>	<b>99.0</b>	<b>18.5</b>	<b>79.5</b>	

<sup>a</sup> As determined by a pollutant-specific EPA reference method, a DEQ-approved alternative, or as determined by DEQ's emissions estimation methods used in this permit analysis.

<sup>b</sup> As determined by multiplying the actual or allowable (if actual is not available) pound-per-hour emission rate by the allowable hours per year that the process(es) may operate(s), or by actual annual production rates.

<sup>c</sup> Includes condensibles.

**AIR QUALITY TIER II OPERATING PERMIT AND PERMIT TO CONSTRUCT NUMBER: P-040319**

<b>Permittee:</b>	Jack B. Parson Companies	<b>Facility ID No:</b>	<b>Date Issued:</b>	<b>June 27, 2005</b>
<b>Location:</b>	Portable	777-00140	<b>Date Expires:</b>	<b>September 18, 2007</b>

**7. GENERAL PROVISIONS**

1. All emissions authorized herein shall be consistent with the terms and conditions of this permit. The emission of any pollutant in excess of the limitations specified herein, or noncompliance with any other condition or limitation contained in this permit, shall constitute a violation of this permit and the *Rules for the Control of Air Pollution in Idaho*, and the Environmental Protection and Health Act, Idaho Code §39-101 et seq.
2. The permittee shall at all times (except as provided in the *Rules for the Control of Air Pollution in Idaho*) maintain and operate in good working order all treatment or control facilities or systems installed or used to achieve compliance with the terms and conditions of this permit and other applicable laws for the control of air pollution.
3. The permittee shall allow the Director, and/or his authorized representative(s), the following upon the presentation of credentials:
  - To enter upon the permittee's premises where an emissions source is located, or in which any records are required to be kept under the terms and conditions of this permit.
  - At reasonable times to have access to and copy any records required to be kept under the terms and conditions of this permit, to inspect any monitoring methods required in this permit, and to require stack emissions testing (i.e., performance tests) in conformance with state-approved or accepted EPA procedures when deemed appropriate by the Director.
4. Except for data determined to be confidential under Section 9-342A, *Idaho Code*, all reports prepared in accordance with the terms of this permit shall be available for public inspection at the appropriate regional office of the Department of Environmental Quality.
5. Nothing in this permit is intended to relieve or exempt the permittee from compliance with any applicable federal, state, or local law or regulation, except as specifically provided herein.
6. In the event of any change in control or ownership of source(s) from which the authorized emissions emanate, the permittee shall notify the succeeding owner or controller of the existence of this permit by letter, a copy of which shall be forwarded to the Director.
7. This permit shall be renewable on the expiration date, provided the permittee submits any and all information necessary for the Director to determine the amount and type of air pollutants emitted from the equipment for which this permit is granted. Failure to submit such information within 60 days after receipt of the Director's request shall cause the permit to become void.
8. The Director may require the permittee to develop a list of operation and maintenance procedures to be approved by DEQ. Such list of procedures shall become a part of this permit by reference, and the permittee shall adhere to all of the operation and maintenance procedures contained therein.
9. The provisions of this permit are severable, and if any provision of this permit to any circumstance is held invalid, the application of such provision to other circumstances, and the remainder of this permit shall not be affected thereby.